

MS45xx Series


Product Definition

PC Board Mountable Pressure Sensor
Combination Temperature and Pressure
Analog Output and I²C or SPI Digital Output
Gage, Differential, Absolute, Compound, Vacuum
3.3 or 5.0Vdc Supply Voltage

MS45xx Series

The MS45xx series is a small, ceramic based, PCB mounted pressure transducer using Measurement Specialties' proprietary UltraStable™ technology (MS4525/MS4525DO) and the latest CMOS sensor conditioning circuitry. This series contains both analog output (MS4515/MS4525) and digital output (MS4515DO/MS4525DO) where the digital output versions feature either I²C or SPI interface and provide 14-bit pressure as well as 11-bit temperature sensing.

It is fully calibrated and temperature compensated with a total error band (TEB) of less than 1.0% over the compensated range. The sensor operates from a single supply of either 3.3 or 5.0Vdc and requires a single external component for proper operation. The rugged ceramic transducer is available in side port, top port, and manifold mount and can measure pressure up to 30inH₂O (MS4515/MS4515DO) and 150psi (MS4525/MS4525DO). The 1/8" barbed pressure ports mate securely with 3/32" ID tubing.



FEATURES

- PCB Mountable
- High Level Analog Output and I²C or SPI Digital Output
- Barbed Pressure Ports
- inH₂O and PSI Pressure Ranges

APPLICATIONS

- Blocked Filter Detection
- Altitude and Airspeed Measurements
- Medical Instruments
- Fire Suppression System
- Panel Meter
- Factory Automation
- Leak Detection
- Vacuum System Process Controls

MS45xx Series

Product Definition

Model	Pressure Ranges	Type (G = Gage A = Absolute D = Differential C = Compound, V = Vacuum)	Output (% Vs)	Supply Voltage (Vs)	Compensated Temperature	Unique Feature
MS4515	0 – 2, 4, 5, 10, 20, 30 inH ₂ O	G, D	10% to 90% 5% to 95%	3.3, 5.0Vdc	0°C to 60°C	inH ₂ O Range Analog Output Temperature & Pressure
MS4515DO	0 – 2, 4, 5, 10, 20, 30 inH ₂ O	G, D	14-bit Digital Word SPI or I ² C	3.3, 5.0Vdc	0°C to 60°C	inH ₂ O Range Digital Output Temperature & Pressure
MS4525	0 - 1, 2, 5, 15, 30, 50, 100, 150psi	G, A, D, C, V	10% to 90% 5% to 95%	3.3, 5.0Vdc	-10°C to +85°C	Low Pressure Range Analog Output UltraStable™
MS4525DO	0 - 1, 2, 5, 15, 30, 50, 100, 150psi	G, A, D, C, V	14-bit Digital Word SPI or I ² C	3.3, 5.0Vdc	-10°C to +85°C	Low Pressure Range Digital Output UltraStable™ Temperature & Pressure

NORTH AMERICA

Measurement Specialties
 45738 Northport Loop West
 Fremont, CA 94538
 Tel: 1-800-767-1888
 Fax: 1-510-498-1578
 Sales: pfg.cs.amer@meas-spec.com

EUROPE

Measurement Specialties
 (Europe), Ltd.
 26 Rue des Dames
 78340 Les Clayes-sous-Bois, France
 Tel: +33 (0) 130 79 33 00
 Fax: +33 (0) 134 81 03 59
 Sales: pfg.cs.emea@meas-spec.com

ASIA

Measurement Specialties
 (China), Ltd.
 No. 26 Langshan Road
 Shenzhen High-Tech Park (North)
 Nanshan District, Shenzhen 518057
 China
 Tel: +86 755 3330 5088
 Fax: +86 755 3330 5099
 Sales: pfg.cs.asia@meas-spec.com

The information in this sheet has been carefully reviewed and is believed to be accurate; however, no responsibility is assumed for inaccuracies. Furthermore, this information does not convey to the purchaser of such devices any license under the patent rights to the manufacturer. Measurement Specialties, Inc. reserves the right to make changes without further notice to any product herein. Measurement Specialties, Inc. makes no warranty, representation or guarantee regarding the suitability of its product for any particular purpose, nor does Measurement Specialties, Inc. assume any liability arising out of the application or use of any product or circuit and specifically disclaims any and all liability, including without limitation consequential or incidental damages. Typical parameters can and do vary in different applications. All operating parameters must be validated for each customer application by customer's technical experts. Measurement Specialties, Inc. does not convey any license under its patent rights nor the rights of others.